



# Protect Bullet Resistant®

## UL 752 Listed and Labeled Levels 1, 2, & 3

### Product Features

<b>Construction:</b>	Fully bonded multi-layer ballistic core		
<b>Core:</b>	Laminated multi-layer		
<b>Door Thickness:</b>	Non-Fire rated	1 3/4"	
	20 Minute Fire Rated	1 3/4"	
<b>Max size non-fire rated:</b>	Single	4/0 x 10/0	
	Pair	8/0 x 10/0	
<b>Max size 20 min fire rated:</b>		<u>Neutral Pressure</u>	<u>Positive Pressure "B"</u>
	Single (20 minute)	4/0 x 10/0	4/0 x 10/0
	Pair (20 minute)	8/0 x 10/0	8/0 x 10/0
	All pairs require a Protect BR Metal Edge / Astragal		
<b>Stiles:</b>	1/2" Stiles prior to factory sizing with matching banded edges		
<b>Faces:</b>	All veneer species, plastic laminates, MDO		
<b>Cross bands:</b>	High density fiberboard (HDF)		
<b>Adhesives:</b>	Type 1 (waterproof)		
<b>Lite Openings:</b>	UL 752 listed frame and glass (must be factory installed). Minimum 6" top rail; 12" bottom rail, 6" hinge stile, 8" lock stile.		
<b>Machining/Finishing:</b>	Prefit, bevel, & factory machining (required) and factory finishing available. (Contact Sales for Machining restrictions)		
<b>Hardware:</b>	Minimum requirement BHMA 1, 2, 3 mortise locks or BHMA 2 cylinder locks. Doors with raceways will include factory installed wires.		
<b>Warranty:</b>	Limited three (3) year - Warranty does not apply to exterior applications		
<b>Labeling Approvals:</b>	Bullet Resistance: Underwriters Laboratories (File # BP10714)		
<b>Fire:</b>	Guardian Fire Testing Laboratories		
<b>Specifications:</b>	Meets UL 752, WDMA & AWI quality standards (contact Sales for label approvals)		
<b>Environmental/LEED Options:</b>	MR4-Recycled content/MR5-Regional Materials/MR6-Rapidly renewable/ MR7 Certified Wood/IEQ4.4-Low-emitting materials (NAUF)		