



Oversize Door Structural Composite Lumber Core

Non-Rated/20 Minute Fire Rated

Product Features

Construction:	Bonded 5 ply Hot Press		
Core:	Structural Composite Lumber Core		
Door Thickness:	Non-rated	1 3/4" - 2 1/4"	
	20 Minute	1 3/4" - 2 1/4"	
Maximum Size:	Single (non-rated)	5/0 x 12/0	
	Pair (non-rated)	10/0 x 12/0	
		<u>Neutral Pressure</u>	<u>Positive Pressure</u>
	Single (20 minute)	5/0 x 10/0	5/0 x 10/0
	Pair (20 minute)	10/0 x 10/0	10/0 x 10/0
	Rated pairs require PPA construction or Metal Edge/Astragal		
Stiles:	7/8" matching hardwood prior to factory trimming (other options available)		
Faces:	All veneer species, medium density overlay (MDO), plastic laminate		
Veneer Matching:	Available in pairs, sets, & transoms (special matching available)		
Cross Bands:	High density fiberboard (HDF)		
Adhesives:	Type 1 (waterproof)		
Max Lite Openings:	Minimum 8" stile, 6" top rail, 12" bottom rail		
Machining/Finishing:	Prefit, bevel, & complete factory machining and factory finishing available		
Warranty:	N/A		
Specifications:	WDMA & AWI quality standards (contact Sales for label approvals)		
Environmental/LEED Options:	MR4-Recycled content/MR6-Rapidly renewable/MR-7 Certified Wood/IEQ4.4-Low-emitting materials (no added urea formaldehyde resins)		