



Mineral Core Lead Lined Door (SafeCore®)

45 / 60 Minute Fire Rated

Product Features

Construction:	Fully bonded core		
Core:	SafeCore® asbestos-free incombustible mineral (blocking available)		
Door Thickness:		<u>Wood Veneer</u>	<u>Plastic Laminate</u>
	1/32" lead	1 3/4"	1 3/4"
	1/16" lead	1 3/4"	1 3/4"
	1/8" lead	1 3/4"	1 3/4"
Maximum Size:		<u>Neutral Pressure</u>	<u>Positive Pressure</u>
	Single	4/0 x 8/0	4/0 x 8/0
	Pair	8/0 x 8/0	8/0 x 8/0
	Requires a lead lined Metal Edge & Astragal		
Lead:	Up to 1/8" total thickness		
Stiles:	Per listing agency specifications		
Top & Bottom Rails:	Per listing agency specifications		
Faces:	All veneer species, medium density overlay (MDO), plastic laminate		
Veneer Matching:	Available in pairs (special matching available)		
Cross bands:	High density fiberboard (HDF)		
Adhesives:	Type 1 (waterproof)		
Max Lite Openings:	Total area of openings not to exceed 1296 sq. in. of visible glass Metal Vision Frames: (Requires approved lead glass and rated glass)		
Machining/Finishing:	Prefit, bevel, & complete factory machining and factory finishing available		
Warranty:	Limited Lifetime - <i>warranty does not apply for exterior applications</i>		
Specifications:	Meets WDMA & AWI quality standards (contact sales for label approvals)		
Environmental/LEED Options:	MR4-Recycled content/MR6-Rapidly renewable/IEQ4.4-Low-emitting materials (no added urea formaldehyde resins)		