



Oversize Door Mineral Core

45 Minute Fire Rated

Product Features

Construction:	Bonded 5 ply Hot Press		
Core:	Asbestos Free Incombustible Mineral (Blocking available)		
	Door Thickness	45 Minute	1 3/4"
Maximum Size:	Single	5/0 x 8/0	
		<u>Neutral Pressure</u>	<u>Positive Pressure "A" & "B"</u>
	Single (45 minute)	5/0 x 8/0	5/0 x 8/0
Stiles:	Matching Hardwood Edges (Fire Approved)		
Top & Bottom Rails:	Per listing agency specifications		
Faces:	All veneer species, plastic laminates		
Cross Bands:	High density fiberboard (HDF)		
Adhesives:	Type 1 (waterproof)		
Lite Openings:	Approved metal vision frame or veneer clad lite bead Total area of visible openings not to exceed 1296 sq in. Maximum continuous dimensions: 36" in width; 54" in length		
Machining/Finishing:	Prefit, bevel, & complete factory machining and factory finishing available		
Warranty:	N/A		
Labeling Approvals:	Guardian Fire Testing Laboratories		
Specifications:	WDMA & AWI quality standards (contact Sales for label approvals)		
Environmental/LEED Options:	MR4-Recycled content/MR6-Rapidly renewable/ MR7-Certified Wood/IEQ4.4-Low-emitting materials (no added urea formaldehyde resins)		