



Structural Composite Lumber Core Center Lead Lined Door

Non-Rated/20 Minute Fire Rated

Product Features

Construction:	Fully bonded core center lead
Core:	Structural composite lumber core
Door Thickness:	Non-rated 1 3/4” Rated 1 3/4” Other thicknesses available
Maximum Size:	Single (non-rated) 4/0 x 8/0 Pair (non-rated) 8/0 x 8/0
Lead:	Up to 1/4” lead thickness (thicker lead requires “Bolted” construction)
Stiles:	7/8” matching hardwood prior to factory trimming (other options available)
Faces:	All veneer species, medium density overlay (MDO), plastic laminate
Veneer Matching:	Available in pairs, sets, & transoms (special matching available)
Cross Bands:	High density fiberboard (HDF)
Adhesives:	Type 1 (waterproof)
Max Lite Openings:	<u>Non-rated:</u> Total sq. in. not to exceed 40% of the surface area of the door with a maximum length not exceeding 50% of the height of the door
Machining/Finishing:	Prefit, bevel, & complete factory machining and factory finishing available
Warranty:	Limited Lifetime - <i>warranty does not apply for exterior applications</i>
Specifications:	Meets WDMA & AWI quality standards (contact sales for label approvals)
Environmental/LEED Options:	MR4-Recycled content/MR6-Rapidly renewable/IEQ4.4-Low-emitting materials (no added urea formaldehyde resins)