



# Oversize Lead Lined

## Non Rated / 20 Minute Fire Rated

### Product Features

<b>Construction:</b>	Bonded 5 ply Hot Press		
<b>Core:</b>	Bonded Particleboard Core (conforming to ANSI A 208.1 1 LD-2) Structural Composite Lumber Core		
<b>Door Thickness:</b>	Non-rated	1 3/4" - 2 1/4"	
	20 Minute	1 3/4" - 2 1/4"	
<b>Maximum Size:</b>	Single (non-rated)	5/0 x 12/0	
	Pair (non-rated)	10/0 x 12/0	
		<u>Neutral Pressure</u>	<u>Positive Pressure</u>
	Single (20 minute)	5/0 x 10/0	5/0 x 10/0
<b>Lead:</b>	Up to 1/4" total thickness		
<b>Stiles:</b>	6" SCL with 7/8" matching hardwood outers (prior to factory trimming) (other options available)		
<b>Top &amp; Bottom Rails:</b>	6" SCL (wider rails available)		
<b>Faces:</b>	All veneer species; medium density overlay (MDO); plastic laminate		
<b>Veneer Matching:</b>	Available in pairs, sets, & transoms (special matching available)		
<b>Cross Bands:</b>	High density fiberboard (HDF)		
<b>Adhesives:</b>	Type 1 (waterproof)		
<b>Lite Openings:</b>	20 min rated 1296 sq/in max. Non-rated contact sales for limitations		
<b>Machining/Finishing:</b>	Prefit, bevel, & complete factory machining and factory finishing available		
<b>Warranty:</b>	N/A		
<b>Specifications:</b>	WDMA & AWI quality standards (contact sales for label approvals)		
<b>Environmental/LEED Options:</b>	MR4-Recycled content/MR-5 Regional Materials/MR6-Rapidly renewable/ MR-7 Certified Wood/IEQ4.4-Low-emitting materials (no added urea formaldehyde resins)		